



CÁNCAMO ROSCADO SOLDADO

Acero Inoxidable Pulido- AISI 304

Nº ART.	G	L1	L2	L3	B1	B2	D	L4	B.L.KG.	KG/100
704370630	M6	57	46	30	25	5,0	13	30	1300	1,8
704370640	M6	66	56	40	25	5,0	13	40	1300	2,8
704370650	M6	76	62	50	25	5,0	13	50	1300	3,0
704370660	M6	87	76	60	25	5,0	13	60	1300	2,6
704370600	M6	126	115	100	25	5,0	13	95	1300	3,7
704370835	M8	66	53	35	25	6,0	15	35	2400	3,8
704370850	M8	80	68	50	25	6,0	15	50	2400	4,9
704370880	M8	110	98	80	25	6,0	15	75	2400	5,5
704370800	M8	130	118	100	25	6,0	15	75	2400	6,5
704371050	M10	85	70	50	30	7,0	16	50	3500	8,7
704371000	M10	135	120	100	30	7,0	16	95	3500	11,0
704371250	M12	90	74	50	30	6,0	18	45	4500	10,2
704371210	M12	140	124	100	30	9,0	18	85	4500	15,0
704371216	M12	200	184	160	30	9,0	18	85	4500	19,0

Nota: Todas las cargas de rotura están determinadas por el ojo (D) y la rosca

