

## HORQUILLA MANUAL

Acero Inoxidable Pulido- AISI 316

Nº ART.	A	L1	L2	L3	L4	CABLE DIM.		D2	KW	KW1	B.L KG.	KG/100
<b>704840603</b>	6	55	63	8	29,0	3	1/8"	6	14	12	750	5,5
<b>704840804</b>	8	62	73	8	35,0	4	5/32"	8	19	14	1500	7,3
<b>704841005</b>	10	72	83	10	42,0	5	-	10	22	16	2180	15
<b>704841206</b>	12	82	95	12	47,5	6	1/4"	12	27	19	3700	23
<b>704841207</b>	12	102	115	13	54,5	7	9/32"	12	29	21	4700	29
<b>704841408</b>	14	103	118	14	58,0	8	5/16"	14	30	24	5600	38
<b>704841610</b>	16	117	135	16	70,0	10	-	16	36	27	8300	63
<b>704841912</b>	18	142	162	16	75,0	12	-	19	42	32	12000	97
<b>704842214</b>	21	162	191	19	88,0	14	-	22	46	36	14000	135
<b>704842516</b>	23	184	217	22	102,0	16	-	25	55	41	23000	215

Nota: Todas las cargas de rotura están determinadas por las mordazas y la rosca

