



BRIDA BLIND

ASME B16.5 1500 Lbs

Diámetro nominal Nominal pipe size	Brida Flange		Resalte Raised face g mm. inches	Taladros Drilling template			Peso aprox. Approx. weight Kg. Pounds
	D mm. inches	b mm. inches		Número	I mm. inches	K mm. inches	
1/2"	120,6 4 3/4	22,2 7/8	34,9 1 3/8	4	22,2 7/8	82,5 3 1/4	1,8 3,9
3/4"	130,2 5 1/8	25,4 1	42,9 1 11/16	4	22,2 7/8	88,9 3 1/2	2,7 6
1"	149,2 5 7/8	28,6 1 1/8	50,8 2	4	25,4 1	101,6 4	3,6 7,9
1 1/4"	158,7 6 1/4	28,6 1 1/8	63,5 2 1/2	4	25,4 1	111,1 4 3/8	4,1 9
1 1/2"	177,8 7	31,8 1 1/4	73,0 2 7/8	4	28,6 1 1/8	123,8 4 7/8	5,9 13
2"	215,9 8 1/2	38,1 1 1/2	92,1 3 5/8	8	25,4 1	165,1 6 1/2	11,3 25
2 1/2"	244,5 9 5/8	41,3 1 5/8	104,8 4 1/8	8	28,6 1 1/8	190,5 7 1/2	15,9 35
3"	266,7 10 1/2	47,6 1 7/8	127,0 5	8	31,7 1 1/4	203,2 8	21,8 48
4"	311,1 12 1/4	54,0 2 1/8	157,2 6 3/16	8	34,9 1 3/8	241,3 9 1/2	33,1 73
5"	374,6 14 3/4	73,0 2 7/8	185,7 7 5/16	8	41,3 1 5/8	292,1 11 1/2	63,5 140
6"	393,7 15 1/2	82,6 3 1/4	215,9 8 1/2	12	38,1 1 1/2	317,5 12 1/2	72,6 160
8"	482,6 19	92,1 3 5/8	269,9 10 5/8	12	44,4 1 3/4	393,7 15 1/2	136 300
10"	584,2 23	107,9 4 1/4	323,8 12 3/4	12	50,8 2	482,6 19	231 510
12"	673,1 26 1/2	123,8 4 7/8	381,0 15	16	54,0 2 1/8	571,5 22 1/2	315 694
14"	749,3 29 1/2	133,3 5 1/4	412,7 16 1/4	16	60,3 2 3/8	635,0 25	445 980
16"	825,5 32 1/2	146,0 5 3/4	469,9 18 1/2	16	66,7 2 5/8	704,8 27 3/4	590 1300
18"	914,4 36	161,9 6 3/8	533,4 21	16	73,0 2 7/8	774,7 30 1/2	794 1750
20"	984,2 38 3/4	177,8 7	584,2 23	16	79,4 3 1/8	831,8 32 3/4	1010 2225
24"	1.168,4 46	203,2 8	692,1 27 1/4	16	92,1 3 5/8	990,6 39	1644 3625