



BRIDA BLIND

ASME B16.5 2500 Lbs

Diámetro nominal Nominal pipe size	Brida Flange		Resalte Raised face g mm. inches	Taladros Drilling template			Peso aprox. Approx. weight Kg. Pounds
	D mm. inches	b mm. inches		Número Number	I mm. inches	K mm. inches	
1/2"	133,35	30,2	34,9	4	22,2	88,9	3
	5 1/4	1 3/16	1 3/8		7/8	3 1/2	7
3/4"	139,7	31,7	42,9	4	22,2	95,2	4,5
	5 1/2	1 1/4	1 11/16		7/8	3 3/4	10
1"	158,75	34,9	50,8	4	25,4	107,95	5
	6 1/4	1 3/8	2		1	4 1/4	12
1 1/4"	184,15	38,1	63,5	4	28,6	130,2	8
	7 1/4	1 1/2	2 1/2		1 1/8	5 1/8	18
1 1/2"	203,2	44,4	73,0	4	31,7	146,05	11
	8	1 3/4	2 7/8		1 1/4	5 3/4	25
2"	234,95	50,8	92,1	8	28,6	171,45	17
	9 1/4	2	3 5/8		1 1/8	6 3/4	39
2 1/2"	266,7	57,1	104,8	8	31,7	196,85	25
	10 1/2	2 1/4	4 1/8		1 1/4	7 3/4	56
3"	304,8	66,7	127,0	8	34,9	228,6	39
	12	2 5/8	5		1 3/8	9	86
4"	355,6	76,2	157,2	8	41,3	273,05	60
	14	3	6 3/16		1 5/8	10 3/4	133
5"	419,1	92,1	185,7	8	47,6	323,8	101
	16 1/2	3 5/8	7 5/16		1 7/8	12 3/4	223
6"	482,6	107,95	215,9	8	54,0	368,3	156
	19	4 1/4	8 1/2		2 1/8	14 1/2	345
8"	552,4	127,0	269,9	12	54,0	438,1	242
	21 3/4	5	10 5/8		2 1/8	17 1/4	533
10"	673,1	165,1	323,8	12	66,7	539,7	465
	26 1/2	6 1/2	12 3/4		2 5/8	21 1/4	1025
12"	762,0	184,15	381,0	12	73,0	619,1	590
	30	7 1/4	15		2 7/8	24 3/8	1300