



BRIDA BLIND

ASME B16.5 600 Lbs

Diámetro nominal Nominal pipe size	Brida Flange		Resalte Raised face g mm. inches	Taladros Drilling template			Peso aprox. Approx. weight Kg. Pounds
	D mm. inches	b mm. inches		Número Number	I mm. inches	K mm. inches	
1/2"	95,2 3 3/4	14,3 9/16	34,9 1 3/8	4	15,9 5/8	66,7 2 5/8	0,9 2
3/4"	117,5 4 5/8	15,9 5/8	42,9 1 11/16	4	19,0 3/4	82,5 3 1/4	1,4 3
1"	123,8 4 7/8	17,5 11/16	50,8 2	4	19,0 3/4	88,9 3 1/2	1,8 4
1 1/4"	133,3 5 1/4	20,6 13/16	63,5 2 1/2	4	19,0 3/4	98,4 3 7/8	2,3 5
1 1/2"	155,6 6 1/8	22,2 7/8	73,0 2 7/8	4	22,2 7/8	114,3 4 1/2	3,6 8
2"	165,1 6 1/2	25,4 1	92,1 3 5/8	8	19,0 3/4	127,0 5	4,5 10
2 1/2"	190,5 7 1/2	28,6 1 1/8	104,8 4 1/8	8	22,2 7/8	149,2 5 7/8	6,8 15
3"	209,5 8 1/4	31,8 1 1/4	127,0 5	8	22,2 7/8	168,3 6 5/8	9,1 20
3 1/2"	228,6 9	34,9 1 3/8	139,7 5 1/2	8	25,4 1	184,1 7 1/4	13,2 29
4"	273,0 10 3/4	38,1 1 1/2	157,2 6 3/16	8	25,4 1	215,9 8 1/2	18,6 41
5"	330,2 13	44,4 1 3/4	185,7 7 5/16	8	28,6 1 1/8	266,7 10 1/2	30,8 68
6"	355,6 14	47,6 1 7/8	215,9 8 1/2	12	28,6 1 1/8	292,1 11 1/2	39 86
8"	419,1 16 1/2	55,6 2 3/16	269,9 10 5/8	12	31,7 1 1/4	349,2 13 3/4	63,5 140
10"	508,0 20	63,5 2 1/2	323,8 12 3/4	16	34,9 1 3/8	431,8 17	104 230
12"	558,8 22	66,7 2 5/8	381,0 15	20	34,9 1 3/8	488,9 19 1/4	134 295
14"	603,2 23 3/4	69,9 2 3/4	412,7 16 1/4	20	38,1 1 1/2	527,0 20 3/4	161 355
16"	685,8 27	76,2 3	469,9 18 1/2	20	41,3 1 5/8	603,2 23 3/4	225 495
18"	742,9 29 1/4	82,6 3 1/4	533,4 21	20	44,4 1 3/4	654,0 25 3/4	286 630
20"	812,8 32	88,9 3 1/2	584,2 23	24	44,4 1 3/4	723,9 28 1/2	367 810
22"	869,9 34 1/4	95,2 3 3/4	641,2 25 1/4	24	47,6 1 7/8	777,9 30 5/8	454 1000
24"	939,8 37	101,6 4	692,1 27 1/4	24	50,8 2	838,2 33	567 1250