



BRIDA THREADED

ASME B16.5 2500 Lbs

Diámetro nominal Nominal pipe size	Brida Flange					Cuello Hub m mm. inches	Resalte Raised face g mm inches	Taladros Drilling template			Peso aprox. Approx. weight Kg. Pounds
	D mm. inches	J mm. inches	b mm. inches	h mm. inches	X mm. inches			Número Number	I mm. inches	K mm. inches	
1/2"	133,35	23,6	30,2	39,7	28,6	42,9	34,9	4	22,2	88,9	3
	5 1/4	0.93	1 3/16	1 9/16	1 1/8	1 11/16	1 3/8		7/8	3 1/2	7
3/4"	139,7	28,95	31,7	42,9	31,7	50,8	42,9	4	22,2	95,2	4
	5 1/2	1.14	1 1/4	1 11/16	1 1/4	2	1 11/16		7/8	3 3/4	9
1"	158,75	35,8	34,9	47,6	34,9	57,1	50,8	4	25,4	107,95	5
	6 1/4	1.41	1 3/8	1 7/8	1 3/8	2 1/4	2		1	4 1/4	12
1 1/4"	184,15	44,45	38,1	52,4	38,1	73,0	63,5	4	28,6	130,2	8
	7 1/4	1.75	1 1/2	2 1/16	1 1/2	2 7/8	2 1/2		1 1/8	5 1/8	18
1 1/2"	203,2	50,5	44,4	60,3	44,4	79,4	73,0	4	31,7	146,05	11
	8	1.99	1 3/4	2 3/8	1 3/4	3 1/8	2 7/8		1 1/4	5 3/4	25
2"	234,95	63,5	50,8	69,8	50,8	95,2	92,1	8	28,6	171,45	17
	9 1/4	2.50	2	2 3/4	2	3 3/4	3 5/8		1 1/8	6 3/4	38
2 1/2"	266,7	76,2	57,1	79,4	57,1	114,3	104,8	8	31,7	196,85	25
	10 1/2	3.00	2 1/4	3 1/8	2 1/4	4 1/2	4 1/8		1 1/4	7 3/4	55