

## CODOS 90º RADIO LARGO ASTM A234 WPB



NW	STANDARD			
	Ø Exterior (mm) D1	Espesor (mm) T	Radio R	Peso Aprox. kgs.
1/2"	21,3	2,77	27,5	0,044
3/4"	26,7	2,87	28,6	0,077
1"	33,5	3,38	38,1	0,154
1 1/4"	42,2	3,56	47,6	0,263
1 1/2"	48,3	3,68	57,1	0,376
2"	60,3	3,91	76,2	0,676
2 1/2"	73,1	5,16	95,2	1,330
3"	88,9	5,49	114,3	2,080
3 1/2"	101,6	5,74	133,4	2,920
4"	114,3	6,02	152,4	3,950
5"	141,3	6,55	190,5	6,670
6"	168,3	7,11	228,6	10,400
8"	219,1	8,18	304,8	20,900
10"	273,0	9,27	381,0	37,000
12"	323,9	9,53	457,2	54,000
14"	355,6	9,53	533,4	69,900
16"	406,4	9,53	609,6	91,200
18"	457,0	9,53	685,8	116,100
20"	508,0	9,53	762,0	143,800
22"	558,8	9,53	838,3	174,600
24"	609,6	9,53	914,4	207,700
26"	660,4	9,53	990,6	244,500
30"	762,0	9,53	1.143,0	326,600
34"	863,6	9,53	1.295,4	420,000
36"	914,4	9,53	1.371,6	471,700
42"	1.066,8	9,53	1.600,2	644,100

NW	XS			
	Ø Exterior (mm) D1	Espesor (mm) T	Radio R	Peso Aprox. kgs.
1/2"	21,3	3,73	27,5	0,280
3/4"	26,7	3,91	28,6	0,330
1"	33,5	4,55	38,1	0,400
1 1/4"	42,2	4,85	47,6	0,490
1 1/2"	48,3	5,08	57,1	0,600
2"	60,3	5,54	76,2	0,940
2 1/2"	73,1	7,01	95,2	1,790
3"	88,9	7,62	114,3	2,780
4"	114,3	8,56	152,4	5,600
5"	141,3	9,53	190,5	9,340
6"	168,3	10,97	228,6	16,000
8"	219,1	12,70	304,8	31,000
10"	273,0	12,70	381,0	49,400
12"	323,9	12,70	457,2	71,400
14"	355,6	12,70	533,4	91,600
16"	406,4	12,70	609,6	120,700
18"	457,0	12,70	685,8	153,000
20"	508,0	12,70	762,0	190,000
24"	609,6	12,70	914,4	275,000
26"	660,4	12,70	990,6	331,000
30"	762,0	12,70	1.143,0	441,300
34"	863,6	12,70	1.295,4	558,500
36"	914,4	12,70	1.371,6	635,000
42"	1.066,8	12,70	1.600,2	853,500