



## BRIDA BLIND

### ASME B16.5 900 Lbs

Diámetro nominal Nominal pipe size	Brida Flange		Resalte Raised face g mm. inches	Taladros Drilling template			Peso aprox. Approx. weight Kg. Pounds
	D mm. inches	b mm. inches		Número Number	I mm. inches	K mm. inches	
1/2"	120,6 4 3/4	22,2 7/8	34,9 1 3/8	4	22,2 7/8	82,5 3 1/4	1,8 4
3/4"	130,2 5 1/8	25,4 1	42,9 1 11/16	4	22,2 7/8	88,9 3 1/2	2,7 6
1"	149,2 5 7/8	28,6 1 1/8	50,8 2	4	25,4 1	101,6 4	3,6 8
1 1/4"	158,7 6 1/4	28,6 1 1/8	63,5 2 1/2	4	25,4 1	111,1 4 3/8	4,1 9
1 1/2"	177,8 7	31,8 1 1/4	73,0 2 7/8	4	28,6 1 1/8	123,8 4 7/8	5,9 13
2"	215,9 8 1/2	38,1 1 1/2	92,1 3 5/8	8	25,4 1	165,1 6 1/2	11,3 25
2 1/2"	244,5 9 5/8	41,3 1 5/8	104,8 4 1/8	8	28,6 1 1/8	190,5 7 1/2	15,9 35
3"	241,3 9 1/2	38,1 1 1/2	127,0 5	8	25,4 1	190,5 7 1/2	13,2 29
4"	292,1 11 1/2	44,5 1 3/4	157,2 6 3/16	8	31,7 1 1/4	234,9 9 1/4	24,5 54
5"	349,2 13 3/4	50,8 2	185,7 7 5/16	8	34,9 1 3/8	279,4 11	39,5 87
6"	381,0 15	55,6 2 3/16	215,9 8 1/2	12	31,7 1 1/4	317,5 12 1/2	52,2 115
8"	469,9 18 1/2	63,5 2 1/2	269,9 10 5/8	12	38,1 1 1/2	393,7 15 1/2	90,7 200
10"	546,1 21 1/2	69,9 2 3/4	323,8 12 3/4	16	38,1 1 1/2	469,9 18 1/2	132 290
12"	609,6 24	79,4 3 1/8	381,0 15	20	38,1 1 1/2	533,4 21	188 415
14"	641,3 25 1/4	85,7 3 3/8	412,7 16 1/4	20	41,3 1 5/8	558,8 22	236 520
16"	704,8 27 3/4	88,9 3 1/2	469,9 18 1/2	20	44,4 1 3/4	615,9 24 1/4	272 600
18"	787,4 31	101,5 4	533,4 21	20	50,8 2	685,8 27	386 850
20"	857,2 33 3/4	107,9 4 1/4	584,2 23	20	54,00 2 1/8	749,3 29 1/2	488 1075
24"	1.041,4 41	139,7 5 1/2	692,1 27 1/4	20	66,7 2 5/8	901,7 35 1/2	918 2025