



## BRIDA LAP JOINT

ASME B16.5 2500 Lbs

Diámetro nominal Nominal pipe size	Brida Flange					Cuello Hub m mm. inches	Taladros Drilling template			Peso aprox. Approx. weight Kg. Pounds
	D mm. inches	J mm. inches	b mm. inches	h mm. inches	r mm. inches		Número Number	I mm. inches	K mm. inches	
1/2"	133,35	22,9	30,2	39,7	3,2	42,9	4	22,2	86,9	3
	5 1/8	0.90	1 3/16	1 9/16	1/8					
3/4"	139,7	28,2	31,7	42,9	3,2	50,8	4	22,2	95,2	4
	5 1/2	1.11	1 1/4	1 11/16	1/8					
1"	158,75	35,05	34,9	47,6	3,2	57,1	4	25,4	107,95	5
	6 1/4	1.38	1 3/8	1 7/8	1/8					
1 1/4"	184,15	43,7	38,1	52,4	4,8	73,0	4	28,6	130,2	8
	7 1/4	1.72	1 1/2	2 1/16	3/16					
1 1/2"	203,2	50,0	44,4	60,3	6,35	79,4	4	31,7	146,05	11
	8	1.97	1 3/4	2 3/8	1/4					
2"	234,95	62,5	50,8	69,8	7,9	95,2	8	28,6	171,45	17
	9 1/4	2.46	2	2 3/4	5/16					
2 1/2"	266,7	75,4	57,1	79,4	7,9	114,3	8	31,7	196,85	25
	10 1/2	2.97	2 1/4	3 1/8	5/16					
3"	304,8	91,4	66,7	92,1	9,5	133,35	8	34,9	228,6	38
	12	3.60	2 5/8	3 5/8	3/8					
4"	355,6	116,8	76,2	107,95	11,1	165,1	8	41,3	273,05	58
	14	4.60	3	4 1/4	7/16					
5"	419,1	144,5	92,1	130,2	11,1	203,2	8	47,6	323,8	95
	16 1/2	5.69	3 5/8	5 1/8	7/16					
6"	482,6	171,45	107,95	152,4	12,7	234,95	8	54,0	368,3	146
	19	6.75	4 1/4	6	1/2					
8"	552,4	222,25	127,0	177,8	12,7	304,8	12	54,0	438,1	220
	21 3/4	8.75	5	7	1/2					
10"	673,1	277,4	165,1	228,6	12,7	374,6	12	66,7	539,7	420
	26 1/2	10.92	6 1/2	9	1/2					
12"	762,0	328,2	184,15	254,0	12,7	441,3	12	73,0	619,1	500
	30	12.92	7 1/4	10	1/2					