



## BRIDA SLIP ON ASME B16.5 1500 Lbs

Diámetro nominal Nominal pipe size	Brida Flange				Cuello Hub m mm. inches	Resalte Raised face g mm. inches	Taladros Drilling template			Peso aprox. Approx. weight Kg. Pounds
	D mm. inches	J mm. inches	b mm. inches	h mm. inches			Número Number	I mm. inches	K mm. inches	
1/2"	120,6	22,3	22,2	31,7	38,1	34,9	4	22,2	82,5	1,8
	4 3/4	0.88	7/8	1 1/4	1 1/2	1 3/8		7/8	3 1/4	4
3/4"	130,2	27,7	25,4	34,9	44,4	42,9	4	22,2	88,9	2,3
	5 1/8	1.09	1	1 3/8	1 3/4	1 11/16		7/8	3 1/2	5
1"	149,2	34,5	28,6	41,3	52,4	50,8	4	25,4	101,6	3,6
	5 7/8	1.36	1 1/8	1 5/8	2 1/16	2		1	4	8
1 1/4"	158,7	43,2	28,6	41,3	63,5	63,5	4	25,4	111,1	4,1
	6 1/4	1.70	1 1/8	1 5/8	2 1/2	2 1/2		1	4 3/8	9
1 1/2"	177,8	49,5	31,8	44,4	69,8	73,0	4	28,6	123,8	5,4
	7	1.95	1 1/4	1 3/4	2 3/4	2 7/8		1 1/8	4 7/8	12
2"	215,9	62,0	38,1	57,1	104,8	92,1	8	25,4	165,1	11,3
	8 1/2	2.44	1 1/2	2 1/4	4 1/8	3 5/8		1	6 1/2	25
2 1/2"	244,5	74,7	41,3	63,5	123,8	104,8	8	28,6	190,5	16,3
	9 5/8	2.94	1 5/8	2 1/2	4 7/8	4 1/8		1 1/8	7 1/2	36