



BRIDA THREADED

ASME B16.5 1500 Lbs

Diámetro nominal Nominal pipe size	Brida Flange					Cuello Hub m mm. inches	Resalte Raised face g mm inches	Taladros Drilling template			Peso aprox. weight Kg. Pounds
	D mm. inches	J mm. inches	b mm. inches	h mm. inches	X mm. inches			Número	I mm. inches	K mm. inches	
1/2"	120,65	23,6	22,2	31,7	22,2	38,1	34,9	4	22,2	82,5	1,8
	4 3/4	0.93	7/8	1 1/4	7/8	1 1/2	1 3/8		7/8	3 1/4	4
3/4"	130,2	28,95	25,4	34,9	25,4	44,4	42,9	4	22,2	88,9	2,4
	5 1/8	1.14	1	1 3/8	1	1 3/4	1 11/16		7/8	3 1/2	5.3
1"	149,2	35,8	28,6	41,3	28,6	52,4	50,8	4	25,4	101,6	3,5
	5 7/8	1.41	1 1/8	1 5/8	1 1/8	2 1/16	2		1	4	7.7
1 1/4"	158,75	44,45	28,6	41,3	30,2	63,5	63,5	4	25,4	111,1	4
	6 1/4	1.75	1 1/8	1 5/8	1 3/16	2 1/2	2 1/2		1	4 3/8	8.8
1 1/2"	177,8	50,5	31,8	44,4	31,7	69,8	73,0	4	28,6	123,8	5,5
	7	1.99	1 1/4	1 3/4	1 1/4	2 3/4	2 7/8		1 1/8	4 7/8	12.1
2"	215,9	63,5	38,1	57,1	38,1	104,8	92,1	8	25,4	165,1	11,3
	8 1/2	2.50	1 1/2	2 1/4	1 1/2	4 1/8	3 5/8		1	6 1/2	25
2 1/2"	244,5	76,2	41,3	63,5	47,6	123,8	104,8	8	28,6	190,5	16
	9 5/8	3.00	1 5/8	2 1/2	1 7/8	4 7/8	4 1/8		1 1/8	7 1/2	36