



BRIDA WELDING NECK

ASME B16.5 1500 Lbs

Diámetro nominal Nominal pipe size	Brida Flange				Cuello Hub		Resalte Raised face g mm inches	Taladros Drilling template			Peso aprox. Approx. weight Kg. Pounds
	D mm. inches	J mm. inches	b mm. inches	h mm. inches	a mm. inches	m mm. inches		Número Number	I mm. inches	K mm. inches	
1/2"	120,6 4 3/4		22,2 7/8	60,3 2 3/8	21,3 0.84	38,1 1 1/2	34,9 1 3/8	4	22,2 7/8	82,5 3 1/4	2,3 5
3/4"	130,2 5 1/8		25,4 1	69,8 2 3/4	26,7 1.05	44,4 1 3/4	42,9 1 11/16	4	22,2 7/8	88,9 3 1/2	2,7 6
1"	149,2 5 7/8		28,6 1 1/8	73,0 2 7/8	33,5 1.32	52,4 2 1/16	50,8 2	4	25,4 1	101,6 4	4,1 9
1 1/4"	158,7 6 1/4		28,6 1 1/8	73,0 2 7/8	42,2 1.66	63,5 2 1/2	63,5 2 1/2	4	25,4 1	111,1 4 3/8	4,5 10
1 1/2"	177,8 7		31,8 1 1/4	82,5 3 1/4	48,3 1.90	69,8 2 3/4	73,0 2 7/8	4	28,6 1 1/8	123,8 4 7/8	5,9 13
2"	215,9 8 1/2		38,1 1 1/2	101,6 4	60,4 2.38	104,8 4 1/8	92,1 3 5/8	8	25,4 1	165,1 6 1/2	11,3 25
2 1/2"	244,5 9 5/8		41,3 1 5/8	104,8 4 1/8	73,1 2.88	123,8 4 7/8	104,8 4 1/8	8	28,6 1 1/8	190,5 7 1/2	16,3 36
3"	266,7 10 1/2		47,6 1 7/8	117,5 4 5/8	88,9 3.50	133,3 5 1/4	127,0 5	8	31,7 1 1/4	203,2 8	21,8 48
4"	311,1 12 1/4		54,0 2 1/8	123,8 4 7/8	114,3 4.50	161,9 6 3/8	157,2 6 3/16	8	34,9 1 3/8	241,3 9 1/2	33,0 73
5"	374,6 14 3/4		73,0 2 7/8	155,6 6 1/8	141,2 5.56	196,8 7 3/4	185,7 7 5/16	8	41,3 1 5/8	292,1 11 1/2	59,0 130
6"	393,7 15 1/2		82,6 3 1/4	171,4 6 3/4	168,4 6.63	228,6 9	215,9 8 1/2	12	38,1 1 1/2	317,5 12 1/2	75,0 165
8"	482,6 19		92,1 3 1/4	212,7 8 3/8	219,2 8.63	292,1 11 1/2	269,9 10 5/8	12	44,4 1 3/4	393,7 15 1/2	125 275
10"	584,2 23		107,9 4 1/4	254,0 10	273,0 10.75	368,3 14 1/2	323,8 12 3/4	12	50,8 2	482,6 19	206 455
12"	673,1 26 1/2		123,8 4 7/8	282,5 11 1/8	323,8 12.75	450,8 17 3/4	381,0 15	16	54,0 2 1/8	571,5 22 1/2	313 690
14"	749,3 29 1/2		133,4 5 1/4	298,4 11 3/4	355,6 14.00	495,3 19 1/2	412,7 16 1/4	16	60,3 2 3/8	635,0 25	426 940
16"	825,5 32 1/2		146,1 5 3/4	311,1 12 1/4	406,4 16.00	552,4 21 3/4	469,9 18 1/2	16	66,7 2 5/8	704,8 27 3/4	567 1250
18"	914,4 36		161,9 6 3/8	327,0 12 7/8	457,2 18.00	596,9 23 1/2	533,4 21	16	73,0 2 7/8	774,7 30 1/2	737 1625
20"	984,2 38 3/4		177,8 7	355,6 14	508,0 20.00	641,3 25 1/4	584,2 23	16	79,4 3 1/8	831,8 32 3/4	930 2050
24"	1168,4 46		203,2 8	406,4 16	609,6 24.00	762,0 30	692,1 27 1/4	16	92,1 3 5/8	990,6 39	1510 3325

Debe ser especificado por el comprador
To be specified by purchaser