



BRIDA WELDING NECK

ASME B16.5 300 Lbs

Diámetro nominal Nominal pipe size	Brida Flange				Cuello Hub		Resalte Raised face g mm inches	Taladros Drilling template			Peso aprox. Approx. weight Kg. Pounds	
	D mm. inches	J mm. inches	b mm. inches	h mm. inches	a mm. inches	m mm. inches		Número Number	I mm. inches	K mm. inches		
1/2"	95,2 3 3/4	15,75 0,62	14,3 9/16	52,4 2 1/16	21,3 0,84	38,1 1 1/2	34,9 1 3/8	4	15,9 5/8	66,7 2 5/8	0,9 2	
3/4"	117,5 4 5/8	20,8 0,82	15,9 5/8	57,1 2 1/4	26,7 1,06	47,6 1 7/8	42,9 1 11/16	4	19,05 3/4	82,5 3 1/4	1,4 3	
1"	123,8 4 7/8	26,7 1,05	17,5 11/16	61,9 2 7/16	33,5 1,32	54,0 2 1/8	50,8 2	4	19,05 3/4	88,9 3 1/2	1,8 4	
1 1/4"	133,35 5 1/4	35,05 1,38	19,05 3/4	65,1 2 9/16	42,2 1,66	63,5 2 1/2	63,5 2 1/2	4	19,05 3/4	98,4 3 7/8	2,3 5	
1 1/2"	155,6 6 1/8	40,9 1,61	20,6 13/16	68,3 2 11/16	48,3 1,90	69,8 2 3/4	73,0 2 7/8	4	22,2 7/8	114,3 4 1/2	3,2 7	
2"	165,1 6 1/2	52,6 2,07	22,2 7/8	69,8 2 3/4	60,45 2,38	84,1 3 5/16	92,1 3 5/8	8	19,05 3/4	127,0 5	4,1 9	
2 1/2"	190,5 7 1/2	62,7 2,47	25,4 1	76,2 3	73,15 2,88	100,0 3 15/16	104,8 4 1/8	8	22,2 7/8	149,2 5 7/8	5,4 12	
3"	209,55 8 1/4	78,0 3,07	28,6 1 1/8	79,4 3 1/8	88,9 3,50	117,5 4 5/8	127,0 5	8	22,2 7/8	168,3 6 5/8	6,8 15	
3 1/2"	228,6 9	90,2 3,55	30,2 1 3/16	81,0 3 3/16	101,6 4,00	133,35 5 1/4	139,7 5 1/2	8	22,2 7/8	184,15 7 1/4	8,2 18	
4"	254,0 10	102,4 4,03	31,8 1 1/4	85,7 3 3/8	114,3 4,50	146,05 5 3/4	157,2 6 3/16	8	22,2 7/8	200,0 7 7/8	11,3 25	
5"	279,4 11	128,3 5,05	34,9 1 3/8	98,4 3 7/8	141,2 5,56	177,8 7	185,7 7 5/16	8	22,2 7/8	234,95 9 1/4	14,5 32	
6"	317,5 12 1/2	154,2 6,07	36,5 1 7/16	98,4 3 7/8	168,4 6,63	206,4 8 1/8	215,9 8 1/2	12	22,2 7/8	269,9 10 5/8	19,0 42	
8"	381,0 15	202,7 7,98	41,3 1 5/8	111,1 4 3/8	219,2 8,63	260,35 10 1/4	269,9 10 5/8	12	25,4 1	330,2 13	30,4 67	
10"	444,5 17 1/2	254,5 10,02	47,6 1 7/8	117,5 4 5/8	273,05 10,75	320,7 12 5/8	323,8 12 3/4	16	28,6 1 1/8	387,3 15 1/4	41,3 91	
12"	520,7 20 1/2	304,8 12,00	50,8 2	130,2 5 1/8	323,85 12,75	374,6 14 3/4	381,0 15	16	31,7 1 1/4	450,8 17 3/4	63,5 140	
14"	584,2 23	Debe ser especificado por el comprador To be specified by purchaser	54,0 2 1/8	142,9 5 5/8	355,6 14,00	425,4 16 3/4	412,7 16 1/4	20	31,7 1 1/4	514,3 20 1/4	81,6 180	
16"	647,7 25 1/2		57,2 2 1/4	146,05 5 3/4	406,4 16,00	482,6 19	469,9 18 1/2	469,9 18 1/2	20	34,9 1 3/8	571,5 22 1/2	113 250
18"	711,2 28		60,3 2 3/8	158,75 6 1/4	457,2 18,00	533,4 21	533,4 21	533,4 21	24	34,9 1 3/8	628,6 24 3/4	145 320
20"	774,7 30 1/2		63,5 2 1/2	161,9 6 3/8	508,0 20,00	587,4 23 1/8	587,4 23 1/8	584,2 23	24	34,9 1 3/8	686,8 27	181 400
22"	838,2 33		66,7 2 5/8	165,1 6 1/2	558,8 22	641,2 25 1/4	641,2 25 1/4	641,2 25 1/4	24	41,3 1 5/8	742,9 29 1/4	211 465
24"	914,4 36		69,8 2 3/4	168,3 6 5/8	609,5 24,00	701,7 27 5/8	701,7 27 5/8	692,1 27 1/4	24	41,3 1 5/8	812,8 32	263 580