



## BRIDA WELDING NECK

### ASME B16.5 900 Lbs

Diámetro nominal Nominal pipe size	Brida Flange				Cuello Hub		Resalte Raised face g mm inches	Taladros Drilling template			Peso aprox. Approx. weight Kg. Pounds
	D mm. inches	J mm. inches	b mm. inches	h mm. inches	a mm. inches	m mm. inches		Número Number	l mm. inches	K mm. inches	
1/2"	120,65 4 3/4		22,2 7/8	60,3 2 3/8	21,3 0,84	38,1 1 1/2	34,9 1 3/8	4	22,2 7/8	82,5 3 1/4	2,3 5
3/4"	130,2 5 1/8		25,4 1	69,8 2 3/4	26,7 1,05	44,4 1 3/4	42,9 1 11/16	4	22,2 7/8	88,9 3 1/2	2,7 6
1"	149,2 5 7/8		28,6 1 1/8	73,0 2 7/8	33,5 1,32	52,4 2 1/16	50,8 2	4	25,4 1	101,6 4	4,1 9
1 1/4"	158,75 6 1/4		28,6 1 1/8	73,0 2 7/8	42,2 1,66	63,5 2 1/2	63,5 2 1/2	4	25,4 1	111,1 4 3/8	4,5 10
1 1/2"	177,8 7		31,8 1 1/4	82,5 3 1/4	48,3 1,90	69,8 2 3/4	73,0 2 7/8	4	28,6 1 1/8	123,8 4 7/8	5,9 13
2"	215,9 8 1/2		38,1 1 1/2	101,6 4	60,45 2,38	104,8 4 1/8	92,1 3 5/8	8	25,4 1	165,1 6 1/2	11,3 25
2 1/2"	244,5 9 5/8		41,3 1 5/8	104,8 4 1/8	73,15 2,88	123,8 4 7/8	104,8 4 1/8	8	28,6 1 1/8	190,5 7 1/2	16,3 36
3"	241,3 9 1/2		38,1 1 1/2	101,6 4	88,9 3,50	127,0 5	127,0 5	8	25,4 1	190,5 7 1/2	14,0 31
4"	292,1 11 1/2		44,5 1 3/4	114,3 4 1/2	114,3 4,50	158,75 6 1/4	157,2 6 3/16	8	31,7 1 1/4	234,95 9 1/4	23,0 51
5"	349,2 13 3/4		50,8 2	127,0 5	141,2 5,56	190,5 7 1/2	185,7 7 5/16	8	34,9 1 3/8	279,4 11	39,0 86
6"	381,0 15		55,6 2 3/16	139,7 5 1/2	168,4 6,63	234,95 9 1/4	215,9 8 1/2	12	31,7 1 1/4	317,5 12 1/2	50,0 110
8"	469,9 18 1/2		63,5 2 1/2	161,9 6 3/8	219,2 8,63	298,4 11 3/4	269,9 10 5/8	12	38,1 1 1/2	393,7 15 1/2	79,4 175
10"	546,1 21 1/2		69,9 2 3/4	184,15 7 1/4	273,05 10,75	368,3 14 1/2	323,8 12 3/4	16	38,1 1 1/2	469,9 18 1/2	118 260
12"	609,6 24		79,4 3 1/8	200,0 7 7/8	323,85 12,75	419,1 16 1/2	381,0 15	20	38,1 1 1/2	533,4 21	147 325
14"	641,3 25 1/4		85,7 3 3/8	212,7 8 3/8	355,6 14,00	450,8 17 3/4	412,7 16 1/4	20	41,3 1 5/8	558,8 22	181 400
16"	704,8 27 3/4		88,9 3 1/2	215,9 8 1/2	406,4 16,00	508,0 20	469,9 18 1/2	20	44,4 1 3/4	615,9 24 1/4	225 495
18"	787,4 31		101,6 4	228,6 9	457,2 18,00	565,1 22 1/4	533,4 21	20	50,8 2	685,8 27	308 680
20"	857,2 33 3/4		107,95 4 1/4	247,65 9 3/4	508,0 20,00	622,3 24 1/2	584,2 23	20	54,0 2 1/8	749,3 29 1/2	376 830
24"	1041,4 41		139,7 5 1/2	292,1 11 1/2	609,6 24,00	749,3 29 1/2	692,1 27 1/4	20	66,7 2 5/8	901,7 35 1/2	680 1500

Debe ser especificado por el comprador  
To be specified by purchaser